




TimberGuard™

Water-Based Urethane Wood Floor Coating




TimberGuard is a single component, water-based urethane wood floor coating that is ideal for high-traffic floors in commercial and residential settings. **TimberGuard** is a highly durable coating that inhibits the growth of stain and odor causing bacteria 24/7.

- Colorless to ensure the natural wood or stain color appears as intended.
- Low VOC formula.
- Oxidative cross-linked formulation provides durability not available in most single component wood floor coatings.
- Quick dry time – normally 2-3 hours.
- Water soluble which allows for easy clean-up.
- Can be applied with a T-bar, Microfiber Roller (1/4 inch nap), or Cut-in Pad.

INDUSTRY-LEADING DURABILITY!

Taber Abrasion Durability Results



Taber Abrasion testing performed by third party independent laboratory.

SURFACES




WOOD FLOORS

TECHNICAL DATA

Description	Water-based polyurethane coating
Appearance	Milky white liquid
Available Sheens	Super Matte, Satin, Semi Gloss, High Gloss
Hardener	Oxygen
pH	7.8
ASTM E70-07	
Specular Gloss (60°)	High Gloss: >85
ASTM D1455-87 (2008)	Semi Gloss: 45-50
	Satin: 20-25
	Super Matte: 5-10
Viscosity (Brookfield)	<100 centipoise
Coverage Rate	500-600 ft ² /gal
Dry Time	2-3 hours for first coat
VOC	<250 g/L
40 CFR Part 59 Subpart D	
Non-volatile solids	32%
ASTM D2834-95 (2008)	
Fragrance	Characteristic
Slip Resistance	UL Certification Pending
ULTM410	
Shelf Life	1 year
ASTM D1791-93 (2008)	
Density	8.7 lb/gal
ASTM D1475-13 (2008)	
Detergent Resistance	Excellent
ASTM D3207-92 (2008)	
Freeze/Thaw	Passes 3 cycles
ASTM D3209-93 (2008)	
Container	1 gal (3,8 liters), wide mouth (63mm) bottle 2.5 gal (9,5 liters) bottle





AMP™ AntiMicrobial Protection is a chemical technology in TimberGuard™ wood floor coatings that inhibits the growth of bacteria.

Bacteria on floors is a common source of odor and stains. **AMP** is an advanced technology within the floor coating that inhibits the growth of stain and odor causing bacteria on the floor surface.



INHIBITS THE
GROWTH OF BACTERIA



CONTINUOUS ANTIMICROBIAL
PROTECTION 24/7



REDUCES
ODORS & STAINS



EPA REGISTERED
ANTIMICROBIAL INGREDIENT

TimberGuard™ floor coatings with **AMP** technology provide continuous antimicrobial protection from the moment the floor coating is dry, 24/7 for the usable life of the coating. No chemical mixing or non-standard floor preparation is required. This unique application of technology inhibits the growth of odor and stain causing bacteria on a cellular level, preventing bacterial microorganisms from feeding, growing, and reproducing.

The application of floor coatings with AMP technology is not a substitute for normal cleaning practices.

