

# HardCore™

## DENSIFYING TREATMENT

A deep penetrating densifier that fills voids, adds structure, and reduces porosity of floors.



SURFACES



### WHY HARDCORE:

## REDUCES POROSITY TO HARDEN SURFACE AND INCREASE DURABILITY

Lithium silicate and potassium silicate blend

## PROLONGS SHINE AND STAIN RESISTANCE

### TECHNICAL DATA

<b>Description</b>	Densifying Treatment	
<b>Appearance</b>	Clear, colorless	
<b>pH</b> ASTM E70-07		11.5
<b>Flash Point</b>	>200°F / >93°C	
<b>Viscosity (Brookfield)</b> @ 68°F (20°C)	<100 centipoise	
<b>VOC</b> 40 CFR Part 59 Subpart D	<50 g/L	
<b>Fragrance</b>	No added fragrance	
<b>Density</b> ASTM D1475-13 (2008)	8.9 lb/gal @ 68°F 1.06 kg/L @ 20°C	
<b>Solubility</b>	Miscible in water	

### DIRECTIONS

Apply with a pump-up sprayer. Spread with a brush or broom to ensure uniform coverage.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at [pioneereclipse.com](http://pioneereclipse.com)

<b>Product Code</b>	422FS	422GL3
<b>Volume</b>	2.50 US gallons	1 US gallon
<b>Shipping Package</b>	2 x 2.5 gallons	3 x 1 gallon
<b>Pallet Quantity</b>	48	60