

LockOut™

HARD FLOOR PROTECTOR

A high performance, penetrating surface treatment that resists stains and enhances gloss.



SURFACES



WHY LOCKOUT:
UNIQUE SILICATE BLEND CREATES A SURFACE THAT IS:

- BREATHABLE
- ULTRA-HARD
- WATER/DUST REPELLENT

GUARDS AGAINST STAINS

CAN BE BURNISHED TO A HIGH GLOSS

TECHNICAL DATA

Description	Hard floor protector
Appearance	Milky, white
pH ASTM E70-07	10.5
Flash Point	>200°F (93°C)
Viscosity (Brookfield) @ 68°F (20°C)	<10 centipoise @ 68°F (20°C)
VOC 40 CFR Part 59 Subpart D	<100 g/L
Fragrance	No added fragrance
Density ASTM D1475-13 (2008)	8.4 lb/gal @ 68°F 1.01 kg/L @ 20°C
Solubility	Miscible in water

DIRECTIONS

NOTE: Do not apply LockOut Hard Floor Protector on floors previously treated with other guards or sealers.

Apply with a pump-up sprayer. Spread evenly with a clean micro-fiber applicator. Allow to dry thoroughly and burnish with a hair blend pad. Repeat with a second coat.

Read all directions and Safety Data Sheet (SDS) before using.

Directions and SDS are available for download at pioneereclipse.com

Product Code	423FS	423GL3
Volume	2.50 US gallons	1 US gallon
Shipping Package	2 x 2.5 gallons	3 x 1 gallon
Pallet Quantity	48	60