



OBS 18DC Orbital Sander

Wood Floor Sanding

- 1 The totally enclosed, fan cooled motor, eliminates overheating and the need for motor cleaning.
- 2 Heavy duty cast aluminum main frame and pad driver plate for added strength.
- 3 Independent dust pickup fan for effective dust containment.
- 4 Dust pipe allows for easy attachment of 3.8 cm or 5.1 cm vacuum hoses for improved dust containment.
- 5 Bristle dust skirt to aid in dust containment (not shown).
- 6 Transparent molded plug has an internal light that serves as a power indicator.

PRODUCT DESCRIPTION

The random-orbital sanding action of the OBS-18DC removes the scratch patterns left by drum or rotary sanders, leaving a smooth, flat floor ready for refinishing. At 3,000 orbits per minute, the OBS-18DC sands faster than any other orbital sander available. With torque-less operation for enhanced operator comfort, the OBS-18DC is perfect for interim "screen and recoat" and fine finish sanding jobs.

RECOMMENDED PRODUCTS



AVAC dust containment systems are the perfect mix of power and portability. At 45 and 98 liter capacities, both models are easy to transport and are available with optional H.E.P.A. filters.



TECHNICAL DATA

Electrical Motor	0.75 kW, Universal, totally enclosed, 230V, 50 Hz
Sanding Path	45.7 cm
Power Cord	12.2 m gray, non-marking rubber
Sanding Pad Size	30.5 cm x 45.7 cm
Abrasive Speed	3,000 orbits per minute
Sound Level	74 dBA
Wheels	(2) 7.6 cm
Size (L x W x H)	46 cm x 51 cm x 114 cm
Machine Weight	56.7 kg
Shipping Weight	66 kg
Warranty	Machine: Parts & Labor - 1 yr* *Excludes consumable wear items

*Specifications are subject to change without notice.

AVAILABLE MODELS

07083A – 230V, 50Hz Orbital Sander w/Dust Control

